

# NEW FUSO



280 PS • 6x4 • Super Mixer

## FJ2528

TRUK  
MITSUBISHI  
**NO.1**  
DI INDONESIA

**ANDALAN BISNIS SEJATI**



## SPECIFICATIONS

Model			<b>FJ2528</b>	
Type			6X4	
<b>DIMENSIONS</b>				
Wheelbase	mm		4,950	
Overall Length	mm		7,460	
Overall Width	mm		2,490	
Overall Height, Approx	mm		2,975	
Tread	front	mm	2,045	
	rear	mm	1,805	
Ground Clearance	mm		234	
Overhang	front	mm	1,460	
	rear	mm	1,050	
<b>WEIGHTS</b>				
Curb Weight*	kg		8,040	
Max. GVW	kg		25,000	
<b>CALCULATED PERFORMANCE</b>				
Max. Speed	km/h		90	
Max. Gradeability	%		62.7	
<b>ENGINE</b>				
Model			6S20 205	
Type			Compression Ignition, Four Stroke, Direct Injection, Turbo Charged Intercooler (air to air) Engine	
Max. Output	PS/rpm		280 / 2200	
Max. Torque	Kgm/rpm		112 / 1200-1600	
Bore x Stroke	mm		102 x 130	
Displacement	cc		6,373	
<b>DRIVE LINE</b>				
Clutch			Dry - Single Plate, Hydraulic Actuated Control with Servo Assistance	
		mm	395	
Transmission	model		G131	
	type		9 Forward & 1 Rev Crawler : 14.570	
	ratio			1st : 9.480 2nd : 6.640
				3rd : 4.820 4th : 3.670
				5th : 2.590 6th : 1.810
			7th : 1.320 8th : 1.000 Rev : 13.860	
Final Gear	model		Fully Floating, Tandem	
	ratio		4.778	
<b>CHASSIS</b>				
Axle Type	front		Reverse Elliot	
	rear		Fully Floating, Tandem	
Tire	front		Single, 11.00 x 20 16PR	
	rear		Dual, 11.00 x 20 16PR	
Suspension	front		Front: Parabolic - Multi Leaf Spring	
	rear		Inverted Semi Elliptic (Bogie) - Multi Leaf Spring	
Brake	service		Pneumatic, Foot Operated, Dual Line Acting on All Wheels	
	parking		Pneumatically Operated Spring Brake Actuator Acting on Rear Axle	
	auxiliary		Exhaust Brake	
Fuel Tank Capacity	litre		255	
Electrical System - Batteries	volt		2x12 - 120Ah	
Cabin			Tilttable	

\*Note: For further improvement and alignment with the latest technology, these specifications may have an update without prior notice.

## DIMENSIONS FJ2528

